

Quick-Stick™



Non-Flammable Spray Adhesive

Premium Quality

- Pressure sensitive
- Methylene chloride based
- High solids content
- Easy application
- Extremely quick tack
- Strong permanent bond
- Meets DOT 39 NRC
- Non-Flammable in wet and dry state
- Exceptional coverage



DUCTMATE®
Industries, Inc.

DESCRIPTION

Quick-Stick is a premium quality, completely non-flammable, pressure sensitive adhesive specifically formulated for a quick permanent tack.

BASIC USE

To provide a versatile convenient means for bonding insulation, or other materials to smooth nonporous surfaces.

SPECIAL CHARACTERISTICS

- Pressure sensitive
- Methylene chloride based
- High solids content
- Easy application
- Extremely quick tack
- Strong permanent bond
- Meets DOT 39 NRC
- Non-Flammable in wet and dry state
- Exceptional coverage

PACKAGING INFORMATION

Part No.	Description	Quantity/Weight
QUICKSTICK40	40 lb Cylinder	1 EA @ 40 lbs.
QUICKSTICK200*	200 lb Cylinder	1 EA @ 200 lbs.
QSSG	Quick-Stick Spray Gun	1 EA @ 1 lb.
QSH6	Quick-Stick 6' Hose	1 EA @ 1 lb.
QSH12	Quick-Stick 12' Hose	1 EA @ 1 lb.
QSH18	Quick-Stick 18' Hose	1 EA @ 2 lbs.

* Available by custom order

APPLICATION

Apply using industry approved spray equipment to smooth nonporous surfaces. Surfaces should be free from all dirt, oil, and grease.

DIRECTIONS: Keep cylinder off of concrete floor during freezing temperatures. For best results use at temperatures between 60°F - 90°F.

1. Make sure all surfaces to be sprayed are clean and free from debris, dust, dirt, grease, etc.
2. Try gun on a test surface to make sure adhesive is flowing.
3. Hold spray gun 8-10 inches from surface to be sprayed.
4. Avoid buildup of adhesive or bubbles. Edges of spray pattern should overlap giving consistent coverage over surface.

FOR PERMANENT BOND: Spray both surfaces, bond activates from moment of contact with adhesive, bond will be permanent after 2 minutes.

TECHNICAL INFORMATION

BASE:	Solvent
SOLVENT:	Methylene Chloride
COLOR:	Green
SOLIDS:	25%
SERVICE TEMPERATURE:	-30°F - 160°F
APPLICATION TEMPERATURE:	60°F - 90°F
STORAGE TEMPERATURE:	Below 120°F
FLAMMABILITY:	None
FLASHPOINT:	None
FREEZE THAW:	Does not apply
COVERAGE:	200 lb: 23,000 sq. ft. - 23,650 sq. ft. 40 lb: 4,000 sq. ft. - 4,600 sq. ft. (Depending on temperature, humidity, and thickness)
BONDING TIME:	1-10 minutes (Depending on application rate)
SHELF LIFE:	1 Year
PACKAGING:	Available in 40, and 200 lb cylinders 200 lb cylinders available by custom order

LIMITED PRODUCT WARRANTY

Ductmate warrants that Quick-Stick, when properly installed and maintained, will be free from defects in material and workmanship, and will comply with all written specifications made by Ductmate at the time of sale. Ductmate's warranty shall run for a period of one year from the date of manufacture.

Warranty Limitation

The warranty stated above is in lieu of all other warranties, express or implied, including but not limited to the implied warranties of MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Although Ductmate may have suggested the product, or provided written or oral advice to the Purchaser, it is the Purchaser's responsibility to test and determine the suitability of Quick-Stick, for the intended use and purpose, and Purchaser and/or its customer assumes all risk and liability whatsoever regarding such suitability.

Limitation of Liability

In the event of a breach of the above warranty, Ductmate's sole obligation, and Purchaser's sole and exclusive remedy, shall be, at Ductmate's option, repair or replacement of any defective products, or refund of an applicable portion of the purchase price. Ductmate shall have no liability for costs of removal or reinstallation of the product. The Purchaser agrees that no other remedy, including but not limited to loss of profits, loss sales, injury to person or property, or any other special, incidental or consequential damages, shall be available to the Purchaser for any claim arising out of this Agreement, regardless of whether such claim is made in contract or in tort, including strict liability in tort. In no event will Ductmate be obligated to pay damages to the Purchaser in any amount exceeding the purchase price that the Purchaser paid to Ductmate for the allegedly defective product.



Charleroi, PA
210 Fifth Street
Charleroi, PA 15022
724-258-0500

Lodi, CA
810 S. Cluff Avenue
Lodi, CA 95240-9141
209-333-4680

*Additional Manufacturing and Warehousing in
Monongahela, PA and Wagoner, OK*

1-800-245-3188 • www.ductmate.com

© Copyright Ductmate Industries, Inc. All rights reserved.



Ductmate Is A Proud Member Of The Following Organizations:



Distributed By: